Ring Terminal RTDs
RTR STYLE

- *Quick Turnaround*
- *DIN CLASS 'A' TOLERANCE, 0.00385 ALPHA IS STANDARD*
- *100 Ω Pt., 1000 Ω Pt. RTDs ARE AVAILABLE*
- *CUSTOM DESIGNS AVAILABLE*

3/8" Screw
1/4" Screw
#10 Screw
#8 Screw
#6 Screw

"L"

ASSEMBLY NO.

| | RTR | 0 | | | 0 | | | | | |

ELEMENT TYPE

F = Thin Film
    100 Ω Platinum
M = Thin Film
    1,000 Ω Platinum
X = Special

STYLE TYPE

06 = # 6 Screw
08 = # 8 Screw
10 = #10 Screw
14 = 1/4" Screw
38 = 3/8" Screw

CIRCUIT TYPE

SINGLE ELEMENT

2 = 2-Wire
3 = 3-Wire
4 = 4-Wire (Only Available in Teflon)

LEADWIRE INSULATION

T = 26 AWG Stranded PFA Teflon® (500°F)
F = 24 AWG Stranded Fiberglass (900°F)
X = Special

LEADWIRE LENGTH "L"

01 to 99 (whole feet)

TERMINATION

S = 2" Split Leads
L = 2" Split Leads w/Spade Lugs
P = Standard Male Plug (400°F)
J = Standard Female Jack (400°F)
M = Miniature Male Plug (400°F)
F = Miniature Female Jack (400°F)
X = Specify Connector Housing

SPECIAL REQUIREMENT

If required, enter "X"
and Consult Factory