CUSTOM THERMOWELLS

WW STYLE

- *CUSTOM BUILT TO CLIENT DRAWING & SPECIFICATION*
- *OTHER MATERIALS AVAILABLE: BRASS, HASTELLOY C®, MONEL, ETC.*
- *PROCESS CONNECTIONS AVAILABLE: SCREWED, WELDED, & FLANGED*
- *STANDARD BORE IS 0.260" & 0.385" (OTHERS AVAILABLE)*

Flanged thermowells are available in a large variety of flange sizes, and configurations that include, but are not limited to, raised face, flat face, and ring type joint.

The socket-weld thermowells are available in a wide variety of process pipe sizes and configurations.

Threaded thermowells are available in a wide variety of process thread sizes and configurations.

Threaded thermowells are available in a wide variety of process thread sizes and configurations.

ASSEMBLY NO.

WW		0								0	

THERMOWELL STYLE

1 = Tapered
2 = Straight
3 = Step-down
4 = Socket-Weld
5 = Flanged

"U" DIMENSION INSERT LENGTH (INCHES)

01 to 99 (whole inches)

"U" DIMENSION INSERT LENGTH (FRACTIONAL INCHES)

0 = 0"
1 = 1/4"
2 = 1/2"
3 = 3/4"

BORE

1 = 0.260"
2 = 0.385"

"E" EXTERNAL THREAD NPT

1 = 1/2" NPT
2 = 3/4" NPT
3 = 1" NPT

FLANGE

0 = No Flange
X = Specify Flange Size & Type

MATERIAL

3 = 316 SS
4 = 304 SS
6 = Alloy 600
7 = Hastelloy C®
X = Specify

SPECIAL REQUIREMENT

If required, enter "X" and Consult Factory