

THERMOCOUPLE CONNECTORS



PANEL JACKS

STANDARD SIZE PANEL JACKS			ROUND HOLE 7/8" DIA. CUTOUT	SPRING CLIP .635" x 1.195" CUTOUT	
TYPE*	THERMOCOUPLE TYPE		SHELL COLOR	SRPJ__-K*	SSPJ__-K*
K	Chromel [®]	Alumel [®]	Yellow	SRPJ-K	SSPJ-K
T	Copper	Constantan [®]	Blue	SRPJ-T	SSPJ-T
J	Iron	Constantan [®]	Black	SRPJ-J	SSPJ-J
E	Chromel [®]	Constantan [®]	Purple	SRPJ-E	SSPJ-E
R*	Pt 13% Rh	Pt	Green	SRPJ-R	SSPJ-R
S*	Pt 10% Rh	Pt	Green	SRPJ-S	SSPJ-S
U**	Copper	Copper	White	SRPJ-U	SSPJ-U
N	Nicrosil [®]	Nisil [®]	Orange	N/A	SSPJ-N
C	W 5% Re	W 26% Re	Red	N/A	N/A

* Type R and S connectors use Copper and Alloy II contacts.

**Uncompensated — used with Type B (Pt 6% Rh - Pt 30% Rh) and 2-wire RTDs.

1.125" DIAMETER




.64" x 1.20"

MINIATURE SIZE PANEL JACKS			ROUND HOLE 5/8" DIA. CUTOUT	SPRING CLIP .318" x .562" CUTOUT	
TYPE*	THERMOCOUPLE TYPE		SHELL COLOR	MRPJ__-K*	MSPJ__-K*
K	Chromel [®]	Alumel [®]	Yellow	MRPJ-K	MSPJ-K
T	Copper	Constantan [®]	Blue	MRPJ-T	MSPJ-T
J	Iron	Constantan [®]	Black	MRPJ-J	MSPJ-J
E	Chromel [®]	Constantan [®]	Purple	MRPJ-E	MSPJ-E
R*	Pt 13% Rh	Pt	Green	MRPJ-R	MSPJ-R
S*	Pt 10% Rh	Pt	Green	MRPJ-S	MSPJ-S
U**	Copper	Copper	White	MRPJ-U	MSPJ-U
N	Nicrosil [®]	Nisil [®]	Orange	N/A	N/A
C	W 5% Re	W 26% Re	Red	N/A	N/A

* Type R and S connectors use Copper and Alloy II contacts.

**Uncompensated — used with Type B (Pt 6% Rh - Pt 30% Rh) and 2-wire RTDs.

.813" DIAMETER



.558" x .938"