

THERMOCOUPLE WIRE & CABLE

TYPE T, E, R, S, B & RTD

TYPE	INSULATION*	AWG #	CATALOG #
T	GLASS 500°C / 900°F	20	GG-TT-20
			GG-TT-20S
		24	GG-TT-24
			GG-TT-24S
			GG-TT-30
	36	GG-TT-36	
	PFA TEFLON® 260°C / 500°F	20	TT(p)-TT-20
			TT(p)-TT-20S
		24	TT(p)-TT-24
			TT(p)-TT-24S
			TT(p)-TT-30
		30	TR(p)-TT-30
			TT(p)-TT-36
		36	TR(p)-TT-36
	KAPTON® 260°C / 500°F		20
	PVC 105°C / 400°F	24	PR-TT-24
	FEP TEFLON® 200°C / 400°F	20	TT(f)-TT-20
	TX	PVC 105°C / 220°F	20
PXFP-TX-20			
PXFP-TX-20S			

TYPE	INSULATION*	AWG #	CATALOG #
E	HI-TEMP GLASS 700°C / 1,300°F	20	HH-EE-20
			GG-EE-20
	GLASS 500°C / 900°F	20	GG-EE-24
			GG-EE-30
			GG-EE-36
			TT(p)-EE-20
	PFA TEFLON® 260°C / 500°F	20	TT(p)-EE-24
			TT(p)-EE-30
			TT(p)-EE-36
			EX
24	PP-EX-24S		
BX	GLASS 500°C / 900°F	20	GG-BX-20
RX& SX		GLASS 500°C / 900°F	20
	24		GG-SX-24
	FEP TEFLON® 200°C / 400°F	20	TT(f)-SX-20
		24	TT(f)-SX-24S
PVC 105°C / 220°F	20	PP-SX-20	
		PXFP-SX-20	
RTD	FEP TEFLON® 200°C / 400°F	22	TT(f)-3CU-22S
			TT(f)-4CU-22S
	GLASS 500°C / 900°F	24	GG-3CU-24S

Please call for:

- Application Assistance
- Calibration Services
- Custom Wire & Cable
- Other Gauge Sizes
- Multipair Extension Cable
- Type 'N' or other calibration
- Type 'T' Validation wire available

Shielded Multipair Extension Cable Available:

4, 8, 12, 16, 20, 24 pair-20 AWG Solid Wire