TRANSITION THERMISTOR PROBE

PT STYLE

- *GENERAL PURPOSE USE AIR, GAS, & LIQUID PROBE*
- *0.1°C & 0.2°C INTERCHANGABLE THERMISTORS*
- *CUSTOM DESIGNS AVAILABLE*



ASSEMBLY NO.

Y	PT				3	2					

ELEMENT TYPE

Y = Specify Thermistor

SHEATH DIAMETER

5 = .125"
7 = .250"
8 = .188"

SHEATH LENGTH "S"

01 to 18 (whole inches)
Consult factory for lengths over 18"

SHEATH MATERIAL

3 = 316 SS Tube Style

CIRCUIT TYPE

SINGLE ELEMENT

2 = 2-Wire

LEAD WIRE INSULATION

P = PVC (220°F)
T = Teflon® (400°F - 500°F)
M = Teflon® w/Flex Armor (400°F - 500°F)
X = Special

LEAD WIRE LENGTH "L"

01 to 99 (whole feet)
Consult factory for lengths over 99'

TERMINATION

S = 2" Split Leads
L = 2" Split Leads w/Spade Lugs
P = Standard Male Plug (400°F)
J = Standard Female Jack (400°F)
M = Miniature Male Plug (400°F)
F = Miniature Female Jack (400°F)
X = Specify Connector Housing

SPECIAL REQUIREMENT

If required, enter "X"
and consult factory